



3-PLATE COUPLING
 TOTAL THICKNESS 3, 6mm
 HUB SECURING BOLTS
 TO BE TIGHTENED TO TORQUE
 OF 24, 9 kgfm (244 Nm)

SAE	TYPE	LB	XG	A
SAE 1	SMU270B	698	352	790
	SMU270CS	698	362	790
	SMU270C	698	362	790
	SMU270D	798	377	890
	SMU270ES	798	402	890
	SMU270E	798	402	890
	SMU270F	823	422	915
SAE 2/3	SMU270GS	823	422	915
	SMU270G	858	442	950
	SMU270H	933	457	1025
	SMU270I	933	467	1025
	SMU270J	933	467	1025

COUPLING DISC						
SAE	BX	P	X	Y	AH	
14	466.72	438.15	8	13.5	25.4	
11.5	352.42	333.38	8	11	39.6	
10	314.32	295.28	8	11	538	

FLANGE (mm)						
SAE	BD	AK	AJ	BF	N	C
3	530	409.58	428.62	11	12	405
2	530	447.68	466.72	11	12	405
1	530	511.18	530.22	14	12	419

VER	MOD	DRW	Date	SAE:	SMU270 (10#)	1:1
Design	App	Date	2021.09	GB/T1804-m	A2	mm
CHK						

SINOCOX