



3mm THICK COUPLING DISC
SECURING SCREWS TO BE
TIGHTENED TO A TORQUE
OF 7,6 kgfm (75 Nm)

DIMENSIONS(mm)

SAE	TYPE	LB	A
SAE 4/5	SMD180B	431.5	551.5
	SMD180C	431.5	551.5
	SMD180DS	521.5	641.5
	SMD180D	521.5	641.5
	SMD180E	521.5	641.5
	SMD180F	593.5	701.5
	SMD180B	443.5	
	SMD180C	443.5	
	SMD180DS	533.5	
	SMD180D	533.5	
	SMD180E	533.5	
	SMD180F	620.5	

COUPLING DISC

SAE	BX	P	X	Y	AH
11.5	352.42	333.38	8	11	39.6
10	314.32	295.28	8	11	53.8
8	263.52	244.48	6	11	62
7.5	241.3	222.25	8	9	30.2
6.5	215.9	200.02	6	9	30.2

FLANGE(mm)

BD	AK	AJ	U°	BF	N	C	
SAE5	356	314.32	333.38	22.5	11	8	238
SAE4	402	361.95	381	15	11	12	238
SAE3	451	409.58	428.62	15	11	12	250

VER	MOD	DRW	Date	SAE:	SMD180	1:1
Design	App	App	Date			A2
CHK		Date	2012/05	GB/T1804-m		mm

2008020

SINOCOX